

CONVERSIONS : 1 km/hr is 5/18 meters per second exactly
 1 km is 1000 meters, 1 hr is 3600 seconds
 1 meter/second is 2.236936292054402 miles/hour
 1 mph = 0.44704 m/s

General Equations of motion (for constant acceleration)

$$D = \frac{(V_i + V_f) T}{2}$$

$$V_f = V_i + A T$$

$$D = V_i T + \frac{1}{2} A T^2$$

$$V_f^2 = V_i^2 + 2 A D$$

$$g = A = 9.81 \text{ m/s/s}$$


For Projectiles/Vectors: $T_x = T_y$, $A_x = 0$, usually, so

Pythagorean: $(\vec{V})^2 = V_x^2 + V_y^2$

$$V_x = \vec{V} \cos(\theta)$$

$$V_y = \vec{V} \sin(\theta)$$

$$\theta = \tan^{-1}(V_y/V_x)$$



X

$$D_x = V_{ix} T$$

$$D_x = \vec{V} \cos(\theta) T$$

Y

$$D_y = V_{iy} T + \frac{1}{2} A_y T^2$$

$$D_y = \vec{V} \sin(\theta) T + \frac{1}{2} A_y T^2$$

$$V_{fy}^2 = V_{iy}^2 + 2 A_y D_y$$

$$V_{fy} = V_{iy} + A_y T$$

V_{fy} at top = zero, $T = 1/2 T_f$ if $D_y = 0$ (up then down)

F(net) = Sum all forces on object F(net) could be

F(net) = Tension-Weight, or F(net) = Pull-Friction, or F(net) = Parallel Force-Pull-friction, etc....

NL I: Inertia

NL II F(net) = mA

$$W = mg$$

NL III F1 = F2

Force(Friction) = $\mu F(\text{Normal})$

$\mu = F_f/F_N$ where μ is the coefficient of friction between two surfaces.

ON RAMP:

Perpendicular Force = $W \cos \theta$

Sliding Force = Parallel Force = $W \sin \theta$

